

474U Touchless Series

Exit Switch

IR Sensor, 4" read range, Wave to Exit Dual LED, illuminated status indication. Control electric locks/strikes, magnetic locks, or automatic door operators. Entry/exit for sanitary environments including: bathrooms, cleanrooms, hospitals, labs, schools, or offices.



474



474D



FEATURES

- Uses IR Sensor Technology; Device is Active with the Simple Wave of a Hand
- Designed to Control Electric Locks/Strikes, Magnetic Locks, or Automatic Door Operators
- Ideal for Use in Sanitary Applications Such as Cleanrooms, Bathrooms, Food Processing, Hospitals and Labs
- Sensing Range up to 4"
- Mounted on a Durable Stainless Steel Plate
- Dual LED, Illuminated Sensor, Red/Green Indicates Inactive/Active Status
- Quick Connect Screwless Terminal Block for Easy Installation



SPECIFICATIONS

Input	25mA (Standby); 70mA (Active) @ 12/24VDC
Output	DPDT 3 Amp Dry Contact Resistive
Activation Time	5 Second or as Long as Sensor is Triggered
LED Color	Standby RED; Active Green
Faceplate	20 Ga Stainless Steel
Range	4"
Weight	3 oz.



MODELS

474U	Sanitary Touchless Exit Switch DPDT, 1 Gang faceplate
474DU	Sanitary Touchless Exit Switch DPDT, 2 Gang faceplate





© 2017 SECURITY DOOR CONTROLS ■ WWW.SDCSECURITY.COM

[t] 800.413.8783 ■ 805.494.0622 ■ [f] 866.215.3138 ■ 801 Avenida Acaso, Camarillo, CA 93012 ■ PO Box 3670, Camarillo, CA 93011

LIT-474 TOUCHLESS 01/17