

Electric Strikes

GK231/233/236M Series

Weatherproof, Preload Solution



NF S 61-937



The GK231/233/236M series European electric strike is designed with its **high preload release capability** that allows smooth operation even under varying loads on the door, such as air-conditioning pressure, changes in the weather, warped doors or doors with weather stripping.

Standard Features

- Stainless steel construction
- Static strength 1,500 lbs (680Kg)
- No frame cutting required (For GK236M)
- Latch monitor (For GK231/233)
- Up to 500 lbs (227Kg) of preload
- Lock monitor
- Fail-safe
- Plug-in terminal block for quick and easy installation
- Adjustable keeper (except GK231)
- Handed (Specify when ordering)

Patents, Approvals, and Listings

- NF S 61-937 Compliant

GK231/233/236M Series European Electric Strikes

Models	Voltage (VDC)	Latch Throw (mm)	Preload (Side Load) 500 lbs.	Mode	Plug-in Terminal Block	Adjustable Keeper	Monitoring Output	Handed
GK231	12 or 24	15	●	Fail-safe	●	—	Lock monitor Latch monitor	●
GK233	12 or 24	11	●	Fail-safe	●	●	Lock monitor Latch monitor	●
GK236M	12 or 24	11	●	Fail-safe	●	●	Lock monitor	●

GK231/233/236M Series Dimensions

