

# Push Plate Exit Buttons

## Disabled Exit Buttons

### Standard Features

- All active target area
- Surface mounted
- Momentary DPDT switch
- Stainless steel faceplate
- Adaptable to wireless (For PBT-900-1)
- Aluminum surface box: 115 x115 x 69.5mm  
Plastic surface box: 130 x 130 x 54mm



 <p><b>PBT-900ALU-1</b></p> <ul style="list-style-type: none"> <li>• Contact rating 5A/125 or 250VAC</li> <li>• Aluminum back box</li> </ul>	 <p><b>PBT-900ALU-2</b></p> <ul style="list-style-type: none"> <li>• Contact rating 5A/125 or 250VAC</li> <li>• Aluminum back box</li> </ul>	 <p><b>PBT-900ALU-3</b></p> <ul style="list-style-type: none"> <li>• Contact rating 5A/125 or 250VAC</li> <li>• Aluminum back box</li> </ul>	 <p><b>PBT-900ALU-4</b></p> <ul style="list-style-type: none"> <li>• Contact rating 5A/125 or 250VAC</li> <li>• Plastic back box</li> </ul>
--	--	---	---

 <p><b>PBT-900-1</b></p> <ul style="list-style-type: none"> <li>• Contact rating 15A/125 or 250VAC</li> <li>• Plastic back box</li> <li>• Available as a wireless exit device</li> </ul>	 <p><b>PBT-900-2</b></p> <ul style="list-style-type: none"> <li>• Contact rating 15A/125 or 250VAC</li> <li>• Plastic back box</li> </ul>	 <p><b>PBT-900-3</b></p> <ul style="list-style-type: none"> <li>• Contact rating 15A/125 or 250VAC</li> <li>• Plastic back box</li> </ul>	 <p><b>PBT-900-4</b></p> <ul style="list-style-type: none"> <li>• Contact rating 15A/125 or 250VAC</li> <li>• Plastic back box</li> </ul>
---	--	---	--

# Push Plate Illuminated Exit Buttons

## Highly Visible, Easy to Activate

### Standard Features

- All active target area
- Momentary SPDT switch
- Stainless steel faceplate
- Plastic back box: 133 x133 x 30mm
- Uses with RF wireless device (For PBT-940WT/960-WT)
- LED Red/Green & Red/Blue illuminations to show door locked or unlocked status



 <p><b>PBT-920</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 15A/125VAC, 15A/125VAC</li> <li>• NO LED</li> <li>• Plastic back box</li> <li>• Stainless steel plate</li> </ul>	 <p><b>PBT-925</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• NO LED</li> <li>• Plastic back box</li> <li>• Blue plate</li> </ul>	 <p><b>PBT-926</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• NO LED</li> <li>• Plastic back box</li> <li>• Blue plate</li> </ul>	
 <p><b>PBT-925BLED</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• Bi-color LED (Green/Blue)</li> <li>• Plastic back box</li> <li>• Blue plate</li> </ul>	 <p><b>PBT-925GLED</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• Bi-color LED (Green/Blue)</li> <li>• Plastic back box</li> <li>• Blue plate</li> </ul>	 <p><b>PBT-926BLED</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• Bi-color LED (Green/Blue)</li> <li>• Plastic back box</li> <li>• Blue plate</li> </ul>	 <p><b>PBT-926GLED</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• Bi-color LED (Green/Blue)</li> <li>• Plastic back box</li> <li>• Blue plate</li> </ul>
 <p><b>PBT-930</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• Bi-color LED (Red/Green)</li> <li>• Plastic back box</li> <li>• Stainless steel plate</li> </ul>	 <p><b>PBT-940WT</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• With wireless receiver S-WPB-025JS</li> <li>• Bi-color LED (Red/Green)</li> <li>• Plastic back box</li> <li>• Stainless steel plate</li> </ul>	 <p><b>PBT-950</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• Bi-color LED (Red/Blue)</li> <li>• Plastic back box</li> <li>• Stainless steel plate</li> </ul>	 <p><b>PBT-960WT</b></p> <ul style="list-style-type: none"> <li>• Momentary SPDT, 0.5A/120VAC, 1A/24VDC</li> <li>• With wireless receiver S-WPB-025JS</li> <li>• Bi-color LED (Red/Blue)</li> <li>• Plastic back box</li> <li>• Stainless steel plate</li> </ul>

# All Function Push Plate Elbow Exit Button



## Standard Features

- Elbow exit button
- Bi-color LED status indicator
- Optional ANSI or European surface mount back box

Models	Electrical	Descriptions/Dimensions	Dimensions
LHS-250	12/24VDC Contact rating 5A/125 or 250VAC DPDT switch	Bi-color LED (Red/Green), Stainless steel faceplate	250 x 95 x 22mm